



UNITED STATES PATENT AND TRADEMARK OFFICE

57
UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/927,558	08/10/2001	George Q. Chen	01-LJ-033	6217

30428 7590 06/14/2005
STMICROELECTRONICS, INC.
MAIL STATION 2346
1310 ELECTRONICS DRIVE
CARROLLTON, TX 75006

EXAMINER

TUCKER, WESLEY J

ART UNIT	PAPER NUMBER
----------	--------------

2623

DATE MAILED: 06/14/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 09/927,558	Applicant(s) CHEN, GEORGE Q.	
	Examiner Wes Tucker	Art Unit 2623	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 14 February 2005.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-29 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 29 is/are allowed.
- 6) ☒ Claim(s) 1-28 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 14 February 2005 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
 Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
 Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|---|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendments and Arguments

1. Applicant's response to the last Office Action, filed June 6, 2004, has been entered and made of record.
2. Applicant has amended Claims 1-3, 10-12, 18-20 and 29. No Claims have been canceled. Claims 1-29 remain pending.

Drawing Objections

3. In view of replacement drawings and discussion provided by Applicant the previously applied drawing objections are withdrawn.

Claims Objections

4. In view of amendments and discussion provided by Applicant, the previously applied Claim objections are withdrawn.

Claim Rejections under 35 USC 112

5. In view of amendments and discussion presented by Applicant, the previously applied Claim rejections under 35 USC 112 are withdrawn.

Claim Rejections under 35 USC 102

6. With regard to Applicant's remarks concerning the newly amended independent Claims 1, 12 and 18, the amendments are not deemed to overcome the cited reference of Chen. Applicant has amended the independent claims to include the new features of "detecting a plurality of pixels in a base image that represents a first view of a scene, wherein the first view is one of at least three views of a scene; determining 3-D depth of the plurality of pixels in the base image by matching correspondence to a plurality of pixels in a plurality of images, each image representing one of the at least three views of the scene wherein each of the at least three views of the scene are situated in a non-linear arrangement and are further oriented in a plurality of non-parallel planes relative to each other.

Applicant argues that the reference of Chen discloses only 2 views of a scene and does not teach that each image represents one of at least three views of the scene. Examiner points to the teapot example (Example 4) at the top left of page 34 in Chen. Chen discloses the 3D calculation using six stereo images. Therefore the reference of Chen still reads on the limitation of at least three views in claims 1, 12 and 18.

Applicant further argues that the images used in the reference of Chen are coplanar and therefore do not meet the limitation of wherein each of the at least three views of the scene are situated in a non-linear arrangement and are further oriented in a plurality of non-parallel planes relative to each other. Examiner points to the example of the teapot again (Example 4) at the top right of page 34. The teapot is placed on a turntable and rotated to capture images at multiple points of rotation. Therefore the

Art Unit: 2623

captured images would likewise not be coplanar. Therefore the reference of Chen still reads on the amended independent Claims 1, 12 and 18.

Applicant also bases arguments concerning dependent claims on the subject matter discussed in regard to independent claims 1, 12 and 18 which have been addressed above.

The rejection of the Claims is therefore maintained and is accordingly made final.

Rejections Under 35 U.S.C. § 102(b)

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

2. Claims 1, 4-9, 12-18, and 21-26 are rejected under 35 U.S.C. 102(b) as being anticipated by [Chen, VSMM99] (Chen and Medioni, "A Volumetric Stereo Matching Method: Application to Image-Based Modeling", IEEE 1999).

3. *The following is in regard to Claim 1.* [Chen, VSMM99] describes a volumetric stereo matching method. The method involves the recovery of depth information – namely, the disparity surface $d(u,v)$ (see [Chen, VSMM99]: Abstract, sentence 1; page

Art Unit: 2623

29, right column, last paragraph¹, sentences 1-3; and page 30, left column, paragraph 1, sentences 2-3) – for pixels of a base image representing a view of a scene. The method comprises at least the following steps:

- (1.a.) Detecting a plurality of pixels in a base image that represents a first view of a scene wherein the first view is one of at least three views of a scene (e.g. capturing images from various viewpoints of the scene). It should be apparent from the various stereo images shown in [Chen, VSMM99] that the volumetric stereo matching method involves this step. Any one of these images can be arbitrarily denoted as a “base image”. *See Also Example 4 on page 34, where 6 views of a teapot are used.*
- (1.b.) Determining 3-D depth of the plurality of pixels in the base image by matching correspondence to a plurality of pixels in a plurality of images each image representing one of the at least three views of the scene wherein each of the at least three views of the scene are situated in a non-linear arrangement and are further oriented in a plurality of non-parallel planes relative to each other. *See Also Example 4 on page 34, where 6 views of a teapot are used. Chen discloses using views of a teapot as it is rotated, the views of which would therefore not lie on parallel planes.*

¹ When referring to paragraphs in the cited references, the convention followed here is that the paragraph number is assigned to paragraphs of a given column (if applicable) or section, sequentially, beginning with the first full paragraph. Paragraphs that carry over to other columns will be referred to as the last paragraph of the column in which they began.

Art Unit: 2623

Steps (1.a.)-(1.b) are typical of any stereo matching applications. The “matching correspondence” is discussed in Section 3.1 of [Chen, VSMM99]. The cross-correlation $\square_{u,v,d}$ is indicative of the matching correspondence between pixels of different images, each of which are representative of disparate views of the scene.

- (1.c.) Tracing pixels (i.e. *surface tracing*) in a virtual piecewise continuous depth surface (i.e. *disparity surface* $d(u,v)$) by spatial propagation ([Chen, VSMM99] section 3.2, paragraph 1, sentence 4) starting from the detected pixels in the base image (i.e. all pixels (u,v) of the base image) by using the matching and corresponding plurality of pixels in the plurality of images (e.g. *seed pixels* that satisfy a given cross-correlation criterion – [Chen, VSMM99] page 31, right column, paragraph 1, sentences 1-2) to create the virtual piecewise continuous depth surface viewed from the base image. Please refer to Section 3 of [Chen, VSMM99].
- (1.d.) Each successfully traced pixel is associated with a depth in the scene viewed from the base image. This follows from the fact that traced pixels lie on the disparity surface. Again, the disparity surface is indicative of the depth of all visible surfaces of a given scene (page 29, right column, last paragraph, sentences 1-3).

In this manner, the a volumetric stereo matching method of [Chen, VSMM99] conforms sufficiently to the method proposed by the Applicant in claim 1.

4. *The following is in regard to Claim 18.* Claim 18 recites essentially the same limitations as claim 1. (The 3D reconstruction instructions merely implement the depth recovery method of Claim 1). Therefore, with regard to claim 18, remarks analogous to those presented above relative to claim 1 are applicable.

5. *The following is in regard to Claim 4.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that adequately conforms to the depth recovery method of Claim 1. The volumetric stereo matching method of [Chen, VSMM99] further involves:

Propagating a front of a virtual piece of a continuous depth surface (e.g. a *surface front* – this terminology is used in sentence 5 of the last paragraph of the right column on page 31) to at least one neighboring pixel (e.g. each *4-neighbor* of (u,v) – Fig. 4 of [Chen, VSMM99]) starting from the detected pixels (e.g. pixel (u,v)) in the base image.

It should be apparent from the algorithm listed in Fig. 4 of [Chen, VSMM99] that the boundary (front) of the disparity surface is propagated. In this manner, the volumetric stereo matching method of [Chen, VSMM99] conforms sufficiently to the method proposed by the Applicant in Claim 4.

6. *The following is in regard to Claim 21.* Claim 21 recites essentially the same limitations as claim 4. (The 3D reconstruction instructions merely implement the depth

recovery method of Claim 4). Therefore, with regard to claim 21, remarks analogous to those presented above relative to claim 4 are applicable.

7. *The following is in regard to Claims 5-6. As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that adequately conforms to the depth recovery method of Claim 4. Tracing the disparity surface according to the volumetric stereo matching method of [Chen, VSMM99] further involves the following:*

- (5.a.) Determining when a boundary is reached between two propagating fronts of virtual pieces of a continuous depth surface ([Chen, VSMM99] page 31, right column, last paragraph, sentence 5).

If the boundaries of two propagating fronts coincide then:

- (6.a.) Comparing the cross-correlations of the two propagating fronts about the reached boundary. This comparison is performed, for example, in the following step shown in [Chen, VSMM99] Fig. 4:

$$\text{disparity}(u', v') = \sum \sum u', v', d' \cdot \sum u', v', d'' \cdot \sum d' \cdot d''$$

Clearly, a comparison of the cross-correlations, $\sum u', v', d'$ and $\sum u', v', d''$ is tantamount to a comparison of the matching costs of the two surface fronts

- (6.b.) The surface front with the greatest cross-correlation prevails ([Chen, VSMM99] page 31, right column, last paragraph, sentence 5). In other words, the propagation of the front with the lower cross-correlation is stopped.

Art Unit: 2623

Step (6.b.) is equivalent to stopping the propagation of the front with the higher compared matching cost². In this manner, the a volumetric stereo matching method of [Chen, VSMM99] conforms sufficiently to both the methods of Claim 5 and the method of Claim 6.

8. *The following is in regard to Claim 22-23.* Claim 22-23 recite essentially the same limitations as claim 5-6, respectively. (The 3D reconstruction instructions of these claims merely implement the depth recovery methods of Claim 5-6). Therefore, with regard to claim 22-23, remarks analogous to those presented above relative to claim 5-6 are respectively applicable.

9. *The following is in regard to Claim 7.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that adequately conforms to the depth recovery method of Claim 1. Tracing the disparity surface according to the volumetric stereo matching method of [Chen, VSMM99] further involves the following:

Propagating a front of a virtual piece of a continuous depth surface to at least one neighboring pixel surrounded by a predefined size window in the continuous depth surface. According to the volumetric stereo matching method of [Chen, VSMM99], the normalized cross-correlation (NCC) over a window (e.g. one with

² To see this recall how the Applicant defines matching cost (page 9, lines 10-15 of the Applicant's disclosure and, in particular, equation (8) on page 17). The matching cost is low for pixels that are likely matches and is high for unlikely matches. The relationship between the matching cost and cross-correlation (NCC) is shown in the Applicant's equation (8). Clearly, a high NCC results in a low matching cost $E(g)$ and indicates a likely match, whereas a low NCC results in a high matching cost and indicates an unlikely match. Therefore, by stopping the propagation of the front with the lower NCC, one has effectively stopped the propagation of the front with the higher matching cost.

dimensions $\square \square \square$ and centered at pixels (u, v) and $(u+d, v)$ is used as the similarity measurement. See Section 3.1 of [Chen, VSMM99].

In this manner, the a volumetric stereo matching method of [Chen, VSMM99] conforms sufficiently to the method of Claim 7.

10. *The following is in regard to Claim 24.* Claim 24 recites essentially the same limitations as claim 7. (The 3D reconstruction instructions merely implement the depth recovery method of Claim 7). Therefore, with regard to claim 24, remarks analogous to those presented above relative to claim 7 are applicable.

11. *The following is in regard to Claim 8-9 and 25-26.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that adequately satisfies the limitations of Claims 7 and 24. The limitations set forth in Claims 8-9 and 25-26 were addressed previously in the discussion above relating to Claims 5-6 and 22-23. The details will not be repeated here.

12. *The following is in regard to Claim 12.* [Chen, VSMM99] discloses a volumetric stereo matching method that includes the following:

- (12.a.) Providing a plurality of seed pixels that represent 3-D depth of the plurality of pixels in the base image view of a scene (i.e. *seed voxels* – [Chen, VSMM99] page 31, right column, paragraph 1).
Seed voxels are determined by matching correspondence to a

plurality of pixels in a plurality of images representing a plurality of views of the scene, wherein the base image is one of at least three views of the scene, each of the at least three views of the scene being situated in a non-linear arrangement and are further oriented in a plurality of non-parallel planes relative to each other (i.e. ensuring that the cross-correlation $\square u, v, d$ between the views satisfies $\square u, v, d \square t1$, $t1$ being a predetermined threshold – [Chen, VSMM99] page 31, right column, paragraph 1, lines 3-4). See also example 4 on page 34 with the 6 rotating views of the teapot.

- (12.b.) Tracing pixels in a virtual piecewise continuous depth surface by spatial propagation starting from the provided plurality of seed pixels in the base image by using the matching and corresponding plurality of pixels in the plurality of images to create the virtual piecewise continuous depth surface viewed from the base image, each successfully traced pixel being associated with a depth in the scene viewed from the base image. The surface tracing was treated above with respect to step (1.c.). See also [Chen, VSMM99] right column, paragraph 2 and Fig. 4.

13. [Chen, VSMM99] presents the volumetric stereo matching method entirely as an algorithm and forgoes any mention of possible hardware implementations. However, the volumetric stereo matching method is shown to have been executed on a computer (e.g. SGI workstation – [Chen, VSMM99] page 34, left column, paragraph 2). In this

case, item (12.a.) would be implemented in computer-readable instructions, say as a "image matching module", and item (12.b.) would be implemented in computer-readable instructions, say as a "propagation module". The "image matching module" and "propagation module" would presumably be resident (electrically coupled) in some memory which is, in turn, coupled to a central processing unit (CPU). In this manner, a computer implementation of the a volumetric stereo matching method of [Chen, VSMM99] would sufficiently conform to the image processing system of Claim 12.

14. *The following is in regard to Claim 13.* As shown above, [Chen, VSMM99] suggests a computer implementation of a volumetric stereo matching method that adequately satisfies the limitations of Claims 12. The disclosed volumetric stereo matching method operates on photographic images (e.g. [Chen, VSMM99] Figs. 2 or 8). This necessitates some means of capturing images, such as a camera(s) (see [Chen, VSMM99] page 34, left column, paragraph 1). In order for the CPU to process the captured images, the camera would have to be somehow electrically coupled (e.g. via some camera interface) to the CPU. Therefore, the features of the image processing system proposed in Claim 13 are inherent to a computer-based implementation of the volumetric stereo matching method of [Chen, VSMM99].

15. *The following is in regard to Claim 14.* As shown above, [Chen, VSMM99] suggests a computer implementation of a volumetric stereo matching method that adequately satisfies the limitations of Claims 12. As mentioned above the "image matching module" and "propagation module" are resident on a memory. Modern memory is implemented as an integrated circuit. All modern CPUs are implemented as

Art Unit: 2623

integrated circuits. In this manner, a computer-based implementation of the a volumetric stereo matching method of [Chen, VSMM99] would adequately satisfy the limitations of Claim 14.

16. *The following is in regard to Claims 15-17.* Claim 15-17 recite essentially the same limitations as claim 5-7, respectively. Therefore, with regard to claim 15-17, remarks analogous to those presented above relative to claim 5-7 are respectively applicable.

Rejections Under 35 U.S.C. § 103(a)

17. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

18. Claims 27-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over [Chen, VSMM99].

19. *The following is in regard to Claim 27.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that adequately satisfies the limitations of Claims 24. Although [Chen, VSMM99] does not explicitly mention associating the normalized cross-correlation (NCC) with a matching cost, the usage of the NCC in

[Chen, VSMM99] suggests that the two are closely related and could indeed be used interchangeably. As mentioned above, [Chen, VSMM99] uses the NCC, $\square u, v, d$ within windows associated with each of the propagating fronts (e.g. windows centered about the voxel (u, v, d) on the surface fronts – [Chen, VSMM99] page 31, left column, lines 1-3 and right column, paragraph 2, sentence 1) to determine which of two coincident surface fronts to continue to propagate ([Chen, VSMM99] page 31, right column, last paragraph, sentence 5). Furthermore, the NCC is indicative of the “correctness” of a match ([Chen, VSMM99], Section 3.2, paragraph 1, sentence 1). All of this suggests that the NCC provides an adequate measure of the matching cost of the propagating surface fronts. Therefore, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to relate the matching cost of the propagating surface fronts to the computation of the NCC or designate the NCC as the matching cost. In either case, the motivation for doing so would have been to utilize the cross-correlative properties of the NCC to evaluate the degree to which voxels, comprising the surface fronts, represent correct matches.

20. *The following is in regard to Claim 28.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that, when modified in the manner suggested above, adequately satisfies the limitations of Claims 26. [Chen, VSMM99] suggests rectification of at least one pair of images corresponding to the base view of the scene and at least one of the other views (e.g. “reference views”). See [Chen, VSMM99] Section 2. Therefore, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to further perform rectification of

at least one pair of images corresponding to the base view of the scene and at least one of the other views (e.g. "reference views"). The result of rectification is that "scanlines [epipolar lines] are parallel in each image, and the corresponding ones are collinear across the images" ([Chen, VSMM99] Section 2, paragraph 1, sentence 2 and last paragraph). This is known to have the effect of greatly simplifying the problem of finding correspondences across stereo images.

21. Claims 2-3 and 19-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over [Chen, VSMM99], in view of [Zhang94] (Zhang, Deriche, Faugeras, and Luong, "A Robust Technique for Matching Two Uncalibrated Images Through the Recovery of Unknown Epipolar Geometry", INRIA 1994).

22. *The following is in regard to Claim 2.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that sufficiently conforms to the depth recovery method proposed in Claim 1. The volumetric stereo matching method of [Chen, VSMM99] operates on multiple images (see, for instance [Chen, VSMM99] Fig. 2 and Fig. 11). That is, the depth recovery according to this method includes the following:

- (2.a.) Detecting a plurality of image pixels in a first image corresponding to a first view of a scene.
- (2.b.) Detecting a plurality of image pixels in at least a second image corresponding to a respective at least a second view of the scene.

The at least a second image deviates from the first image as a result of camera relative motion. This is typical of stereo matching algorithms (see also [Chen, VSMM99] page 34, *Example 4*).

As noted above, the volumetric stereo matching method of [Chen, VSMM99], like most stereo matching methods, involves determining correspondences between a plurality of pixels in a first image and a plurality of pixels of at least a second image. In other words, the method of [Chen, VSMM99] further involves:

- (2.c.) Determining a first two-view correspondence between the plurality of detected image pixels in the first image and a plurality of detected image pixels in one of the at least a second image resulting in a first potential match set of candidate image pixels between the first image and the one of the at least a second image.

This process involves the evaluation of the cross-correlation

$\square u, v, d$ as discussed above with regard to step (1.b.).

23. [Chen, VSMM99] further suggests subsequently computing the *projective reconstruction* from the derived correspondence information in order to reconstruct the projective 3D structure of the observed scene ([Chen, VSMM99] Section 4, paragraph 1).

24. [Chen, VSMM99] does not, however, expressly show or suggest:

- (2.d.) Concatenating a plurality of two-view match sets to form a first multiple-view potential match set; and

- (2.e.) Determining a second multiple-view potential match set that is a

refinement of the first multiple-view potential match set.

25. [Zhang94], on the other hand, discloses a stereo matching method. Stereo matching across disparate views of a scene is generally a fundamental step in depth recovery. The stereo matching method involves at least the following steps (refer to [Zhang94] Section 6.3 on pages 16-19):

- (2.c.) Determining an initial set of correspondences or matches (e.g. a first two-view correspondence) between the plurality of detected image pixels in the first image and a plurality of detected image pixels in one of the at least a second image resulting in a first potential match set of candidate image pixels (e.g. *candidate matches* - see, for example, [Zhang94] page 10, Section 5, paragraph 1, lines 1-2) between the first image and the one of the at least a second image.
- (2.d.) Removing outliers from the initial set of matches (i.e. determining a "multiple-view correspondence" between the plurality of detected image pixels in the first image and the plurality of detected image pixels in the at least a second image). See, for example, [Zhang94] page 18, line 24³, in conjunction with the equations for the weights w_i on pages 17-18. In this manner, the set of matches or correspondences thus obtained (e.g. the "multiple-view correspondences") represents a refinement of the "first two-view

³ Lines are counted sequentially from the top beginning with 1. An equation is treated as a single line, regardless of its length.

correspondence", resulting in a "second potential match set" of candidate image pixels between the first image and the at least a second image.

- (2.e.) The "second potential match set" is based at least in part on a computation of reprojection error (e.g. *residual* r_i – [Zhang94] page 17, paragraphs 1-2) for matched pixels that resulted from "the difference between the i -th observation and its fitted value"⁴ ([Zhang94] page 17, paragraph 1, lines 1-2).

26. The teachings of [Chen, VSMM99] and [Zhang94] are combinable because they are analogous art. Specifically, both [Chen, VSMM99] and [Zhang94] disclose methods for stereo matching. Therefore, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to use the methodology of [Zhang94] – in particular, steps (2.d.)-(2.e.) above – to refine the initial set of correspondences derived according to the method of [Chen, VSMM99]. It would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, that, in applying this refinement process to method of [Chen, VSMM99], the *fitted values* become the reprojected projective points that delimit the projective structure of the observed scene (i.e. "matched pixels that resulted from a projective reconstruction of the first potential match set"). The motivation for using the method of [Zhang94], in this manner, would have been to detect and remove *outliers* (e.g. *bad locations* and/or *false*

⁴ It should be understood that the *fitted value* in this case is a projection of the matched pixels into some view being evaluated and the observation is the respective candidate point correspondences $\{(m_{1i}, m_{2i})\}$. See [Zhang94] page 17, last paragraph.

matches – [Zhang94] page 16, last paragraph) from the initial set of candidate matches (e.g. those obtained via step (2.c.) above). See [Zhang94] Section 6.3.

27. *The following is in regard to Claims 19.* Claim 19 recites essentially the same limitations as claim 2. (The 3D reconstruction instructions merely implement the depth recovery method of Claim 2). Therefore, with regard to claim 19, remarks analogous to those presented above relative to claim 2 are applicable.

28. *The following is in regard to Claim 3.* As shown above the methods of [Chen, VSMM99] and [Zhang94] can be combined to satisfy the limitations of Claim 2. [Zhang94] further disclose that the “outlier-less” set of correspondences (i.e. the “second potential match set”) is based at least in part on a least median of squares computation (*LMedS* – [Zhang94] Abstract and page 17, lines 4-7 and paragraph 2) of the reprojection errors (i.e. *residuals* r_i – see above) related to matched pixels in the *first* potential match set. *LMedS*, as put forth by [Zhang94], has an advantage over other methods in that it “is very robust to false matches as well as outliers due to bad localization” ([Zhang94] page 17, paragraph 1, last sentence). Therefore, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to use the *LMedS* of [Zhang94] to detect and remove outliers from the first potential match set.

29. *The following is in regard to Claim 20.* Claim 20 recites essentially the same limitations as claim 3. (The 3D reconstruction instructions merely implement the depth

recovery method of Claim 3). Therefore, with regard to claim 20, remarks analogous to those presented above relative to claim 3 are applicable.

30. Claims 10-11 and are rejected under 35 U.S.C. 103(a) as being unpatentable over [Chen, VSMM99], in view of [Okutomi93] (Okutomi and Kanade "A Multiple-Baseline Stereo", IEEE 1993), in further view of [Lewis95] (Lewis, "Fast Normalized Cross-Correlation", 1995).

31. *The following is in regard to Claim 10.* As shown above, [Chen, VSMM99] discloses a volumetric stereo matching method that sufficiently conforms to the depth recovery method proposed in Claim 9. As discussed above, the method of [Chen, VSMM99] involves the computation of the NCC between a first image window of a pre-determined size in the base view, and a second image window of the same pre-determined size in other views ([Chen, VSMM99] Section 3.1). It was also show above that the NCC is intimately related to the matching cost. Despite this, [Chen, VSMM99] does not expressly show or suggest that the matching cost is determined by computing the summation of all the normalized cross-correlations between a first image window of a pre-determined size in the base view, and a second image window of the same pre-determined size in a reference view.

32. [Okutomi93] disclose a stereo matching method that uses multiple stereo pairs with various baselines for the purposes of depth recovery ([Okutomi93] Abstract sentence 1). According to [Okutomi93], the summation of the sum of squared

Art Unit: 2623

differences (SSD) from multiple stereo pairs can be used to indicate the "correctness" of a set of matching points (pixels). See [Okutomi93] page 353 (right column, paragraph 3, first and last sentence), page 354, (left column, lines 7-10), page 355 (Section B, paragraph 2, sentence 1), and equation (39) on page 362. This summation is analogous to a matching cost in that it approaches a minimum for correct matches ([Okutomi93] page 353, right column, paragraph 3, last sentence). According to equation (39) the computation is made within a predetermined window W belonging to each of the stereo images ([Okutomi93] page 354, right column, paragraph 1, line 4). In summary, [Okutomi93] shows a "matching cost" determined by computing the summation of all the SSD's between a first image window of a pre-determined size in the base view and a second image window of the same pre-determined size in other views (e.g. "reference views"). Given this, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to use a "matching cost" (i.e. a measure of the similarity or "correctness" of a match) determined by computing the summation of all the SSD's between a first image window of a pre-determined size in the base view and a second image window of the same pre-determined size in other views (e.g. "reference views"). As pointed out by [Okutomi93], this would have the effect of advantageously reducing global mismatches ([Okutomi93], page 353, right column, paragraph 3, first sentence).

33. Note that the SSD and NCC are closely related mathematically. As measures of similarity among regions of images, they are functionally equivalent. See [Lewis95] Section 2, paragraph 1. Furthermore, it can also be shown that the process of

minimizing the SSD and maximizing the NCC are in fact equivalent operations. All of this suggests that SSD and NCC are essentially interchangeable. Moreover, the NCC has the advantage over the SSD in that it is invariant to "changes in image amplitude such as those caused by changing lighting conditions across the image sequence" ([Lewis95] page 2, lines 8-17). Since lighting conditions are likely to vary across the various stereo images, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to substitute the NCC for the SSD in the stereo matching method of [Okutomi93]. This would yield a "matching cost" determined by computing the summation of all the *NCC*'s between a first image window of a pre-determined size in the base view and a second image window of the same pre-determined size in other views (e.g. "reference views").

34. The teachings of [Chen, VSMM99] and [Okutomi93] are combinable because they are analogous art, namely, the art of stereo matching. The teachings of [Lewis95] are applicable to both the methods of [Chen, VSMM99] and [Okutomi93] because all relate generally to correlative approaches for evaluating the similarity of windowed-regions belonging to a collection of images of a scene. Combining these teachings as suggested above yields a method that conforms sufficiently to that of claim 10.

35. *The following is in regard to Claim 11.* As shown above the teachings of [Chen, VSMM99], [Okutomi93], and [Lewis95] can be combined so as to yield a method that adequately satisfies the limitations of Claim 10. [Chen, VSMM99] suggests rectification of at least one pair of images corresponding to the base view of the scene and at least

Art Unit: 2623

one of the other views (e.g. "reference views"). See [Chen, VSMM99] Section 2.

Therefore, it would have been obvious to one of ordinary skill in the art, at the time of the applicant's claimed invention, to further perform rectification of at least one pair of images corresponding to the base view of the scene and at least one of the other views (e.g. "reference views"). The result of rectification is that "scanlines [epipolar lines] are parallel in each image, and the corresponding ones are collinear across the images" ([Chen, VSMM99] Section 2, paragraph 1, sentence 2 and last paragraph). This is known to have the effect of greatly simplifying the problem of finding correspondences across stereo images.

Allowable Subject Matter

Objections, Allowable Subject Matter

36. Claim 29 is found to be allowable in view of the presented amendment and discussion in view of the previously applied 112 rejection.

37. The following is a statement of reasons for the indication of allowable subject matter. As shown above, [Chen, VSMM99] discloses:

- (29.a.) Tracing at least one parameter surface (e.g. disparity surface),
each of the at least one parameter surface traced starting from at
least one predetermined seed pixel point.

However, no prior art methods were encountered that involved or even suggested the step of:

- (29.b.) Calculating a derivative of function $E(g)$ with respect to parameter g by using finite difference to minimize the equation of $E(g)$ put forth in Claim 29.

Conclusion

Applicant's amendment necessitated the new grounds of rejection presented in the Office Action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37CFR 1.136(a).


A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Wes Tucker whose telephone number is 703-305-6700. The examiner can normally be reached on 9AM-5PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amelia Au can be reached on 571-272-7427. The fax phone number for the organization where this application or proceeding is assigned is 571-272-7414.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Wes Tucker
6-8-05


AMELIA M. AU
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600